



DC-2300

Entrance to
professional card printing



HIGHLIGHTS AT A GLANCE:

- High resolution printing with 300 x 1200 dpi
- Fast print speed for up to 900 cards/hour in monochrome and up to 180 cards/hour in colour
- Edge-to-Edge printing
- Easy to use
- Compact design with small footprint

DC-2300

The DASCOS DC-2300 is a direct thermal card printer especially designed for front-desk applications. With a compact design this printer doesn't use much space on your desk but delivers fast and crisp results. With a resolution of up to 300 x 1.200 dpi fine details are visible and with a print speed of up to 180 cards/hour in colour even large print jobs can be done in a short time.


Thanks to Edge-to-Edge printing, the DC-2300 is the perfect partner for employee ID, membership or loyalty cards. Easy exchangeable ribbons and an OLED display on the front informing about the actual status makes the daily work simple.

TECHNICAL DATA

Print Method	Direct thermal technology
Resolution	up to 300 x 1200 dpi
Print Capability	Single Side, Double Side (Factory build), Edge-to-Edge
Print Speed	Single Side: 180 cards/hour (YMCKO) or 900 cards/hour (Monochrome K) Double Side: 135 cards/hour (YMCKOK)
Interfaces	USB (2.0), Ethernet (10/100)
Card Thickness	0,25 - 1,1 mm (10 - 50 mil)
Security Features	RFID ribbon, custom watermarks (BMP)
Card Loading	Auto card feeder for 100 cards (0,76 mm thickness) Manual feed: single card
Card Output	75 cards (rear side), 25 cards (front side)
Card Types	PVC, PET, PET-G, ABS, Teslin® 85,6 x 53,98 mm (ISO ID-1/CR-80 size)
Consumables	Ribbon YMCKO (500 Images), Ribbon YMCKOO (400 Images), Ribbon YMCKOK (400 Images), Ribbon ½YMC KO (600 Images), Ribbon K (2.000 Images), Ribbon K eco (2.000 Images), Ribbon K Paper (2.000 Images) Ribbon White (2.000 Images)
Cleaning Set	Cleaning Card Cleaning Roller
Physical Weight	6,2 kg
Physical Size	Single Side: 199 x 352 x 209 mm (W x D x H) Double Side: 199 x 400 x 220 mm (W x D x H)
Noise	52 dB(A) while printing 35 dB(A) in standby
Power Voltage	Auto wide ranging, 100 - 240 V AC - 50/60 Hz
Environment	Printing: +15° to +35° C Temperature; 35 - 65% Humidity Storage: -5° C to +70° C Temperature; 20 - 70% Humidity
Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022
Warranty	For more details please contact your local dealer



Modular design allows you to print dual-sided without compromising its small footprint size



Different ribbon cassettes for specific demands make the handling easy

CHINA

Jiangmen Dascom Computer Peripherals Co., Ltd.
No.399,Jinxing Road | Jianghai District | Jiangmen City
Guangdong Province | CHINA
Tel.: +86 0750-3868008 | Fax: +86 0750-3868011
info.cn@dascom.com | www.dascom.com

APAC

DASCOS AP Pte. Ltd.
2 Jurong East Street 21 | # 05-42, IMM Building
Singapore 609601
Tel.: +65 6760 8833 | Fax: +65 67601066
info.sg@dascom.com | www.dascom.com.sg

AMERICAS

DASCOS Americas
34 Lakeview Court | Verona | Virginia, 24482 | USA
Tel.: +1 (877) 434-1377
info.us@dascom.com | www.dascomamericas.com

EMEA

DASCOS Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info.de@dascom.com | www.dascomeurope.de