



## DL-200

Indispensable in many places

### HIGHLIGHTS AT A GLANCE:

- Easy and Quick media loading
- Variety of interfaces
- Supports ZPL and EPL emulation
- Small footprint



# DL-200

Tally Dascom's DL-200 thermal transfer printer offers reliability, precision and performance in a compact size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media and ribbon loading.

The DL-200 is easily integrated into existing systems as there are several interfaces also available. In addition to this, the DL-200 is also available with an optional cutter.

## TECHNICAL DATA

<b>Print Speed</b>	5 ips (127 mm/Sek.)
<b>Print Width</b>	4" (108 mm)
<b>Print Method</b>	Direct Thermal or Thermal Transfer
<b>Resolution</b>	203 dpi
<b>Fonts</b>	Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM
<b>Print head Lifetime</b>	30 km or 6 months
<b>Memory</b>	8 MB Flash, 8 MB SDRAM
<b>Interfaces Standard</b>	USB (2.0 Full Speed)
<b>Interfaces Optional</b>	Serial (RS-232C), Parallel (IEEE 1284), Ethernet (10/100)
<b>Emulations</b>	ZPL II, EPL
<b>Consumables</b>	Ribbon, Direct Thermal/ Thermal Transfer paper and labels
<b>Ribbon</b>	Width: 30 - 110 mm; Length: 74 m Core diameter: 0,5" (12,7 mm); Outside diameter: 37 mm
<b>Media</b>	Width: 25 - 120 mm; Thickness: 0,05 - 0,32 mm Core diameter: 1" or 1,5" (25,4 mm or 37 mm); Outside diameter: 5" (127 mm)
<b>Sensors</b>	Black Mark, Label Gap, Ribbon
<b>Barcode</b>	1D: Code 11, Interleaved 2-of-5, Code 39, Code 49, Code 93, Code 128, Planet Code, EAN 8, EAN 13, UPC-E, UPC-A, Industrial 2 of 5, Standard 2 of 5, Codabar, MSI, Plessey 2D: PDF 417, MaxiCode, QR Code, Data Matrix
<b>Physical Weight</b>	1,8 kg
<b>Physical Size</b>	207 x 241 x 172 mm (W x D x H)
<b>Power Voltage</b>	100 - 240 V AC - 50/60 Hz
<b>Temperature</b>	+5° to +40° C
<b>Humidity</b>	10% to 98% (non condensing)
<b>Print Volume</b>	up to 300 m/day
<b>Printer Driver</b>	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022
<b>Options</b>	Models with cutter or peeler; Serial, Parallel, Ethernet interface
<b>Warranty</b>	For more details please contact your local dealer

### Configurations:

- **DL-200** Standard Product (USB only)
- **DL-200 Ser** Model with USB & ser. interface
- **DL-200 Par** Model with USB & par. interface
- **DL-200 Eth** Model with USB & Ethernet interface

#### CHINA

Jiangmen Dascom Computer Peripherals Co., Ltd.  
No.399, Jinxing Road | Jianghai District  
Jiangmen City, Guangdong Province | China  
Tel: +86 0750-3868008 Fax: +86 0750-3868011  
info.cn@dascom.com | www.dascom.com

#### AMERICAS

DASCOM Americas.  
34 Lakeview Court | Verona  
Virginia, 24482 | USA  
Tel: +1(877)434-1377  
info.us@dascom.com | www.dascomamericas.com

#### APAC

DASCOM AP Pte. Ltd.  
2 Jurong East Street 21 | #05-42, IMM Building  
Singapore 609601  
Tel: +65 6760 8833 Fax: +65 67601066  
info.sg@dascom.com | www.dascom.com.sg

#### EMEA

DASCOM Europe GmbH.  
Heuweg 3  
89079 Ulm | GERMANY  
Tel: +49731 2075-0 Fax: +49 731 2075-100  
info.de@dascom.com | www.dascomeurope.de