



DP-230LFast printing, minimum size





HIGHLIGHTS AT A GLANCE:

- Operates with comfort thanks to its OLED screen
- Its ultraportable size and useful interface allows to use it with only one hand
- Easy paper loading
- Up to 3 inches per second



DP-230L

The DP-230L is a 80 mm thermal mobile printer with long battery life, reliable performance and compatibility with BT and WIFI. It is of small weight for users to carry it with them. Its weight including the battery is only 400 g and only 111 x 112 x 56 mm in size.

Prints up to 150 meters of paper due to its large capacity lithium battery of 7.2 V / 2200 mAH. You will no longer have to reload the printer during a work day. Easily configure your printer and check the battery status thanks to its high contrast and brightness OLED display. It is compatible with Android, IOS, Windows CE and other operating systems via BT or WiFi.

TECHNICAL SPECIFICATIONS

Print speed	Up to 3 inch/sec (76,2 mm/sec)
Resolution	203 dpi (8 dots/mm)
Lifetime print head	50 km
Memory	40 MB FLASH, 32 MB DRAM
Print width	Up to 72 mm
Interfaces Standard	USB 2.0
Interfaces Optional	BT or WiFi (IEEE 802.11.b/g/n)
Sensors	Low battery, end of paper, paper gate
Administration	Via LED screen or web panel
Emulations	ESC/POS, ZPL II, CPCL
Roll diameter	Max. outside diameter 45 mm
Paper width	80 mm
Paper thickness	0,06 - 0,15 mm
Battery	Rechargeable 3 cells Lithium-Ion (2.200 mAh)
	Endurance more then 150 m per charge
	Charging time 2 hours
Weight	0,4 kg (incl. battery)
	o, r kg (mor. battery)
Dimensions	111 x 112 x 56 mm (W x D x H)
Dimensions Temperature	
	111 x 112 x 56 mm (W x D x H)
Temperature	111 x 112 x 56 mm (W x D x H) -10° to +45°C (printing); -25° to 65° C (storage)
Temperature Humidity	111 x 112 x 56 mm (W x D x H) -10° to +45°C (printing); -25° to 65° C (storage) 0% to 65% (printing); 0% to 98% (storage)
Temperature Humidity MTBF	111 x 112 x 56 mm (W x D x H) -10° to +45°C (printing); -25° to 65° C (storage) 0% to 65% (printing); 0% to 98% (storage) 10.000 hours Windows 8/8.1/10/11 and Server 2012/2016/2019/2022;
Temperature Humidity MTBF Drivers	111 x 112 x 56 mm (W x D x H) -10° to +45°C (printing); -25° to 65° C (storage) 0% to 65% (printing); 0% to 98% (storage) 10.000 hours Windows 8/8.1/10/11 and Server 2012/2016/2019/2022; Android; iOS (only WiFi)

Configurations:

• DP-230L Receipt & label model

 DP-230L BT Receipt & label model with BT • DP-230L WiFi Receipt & label model with WiFi