









## **HIGHLIGHTS AT A GLANCE:**

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 24 wires print head for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- USB Host interface for easy firmwareupdate
- User-friendly, backlit illuminated LC display



## 2600+

The new Tally Dascom 2600+ is the **further developed variant** of the successful Tally Dascom 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 10 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB, Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only **up to 20% faster**, but also allows for a **noise reduction of up to 2 decibels** thanks to its design.

## **TECHNICAL DATA**

Print speed		683 cps	
	•	10 / 12 / 15 cpi	
		600 / 683 / 683 cps 513 / 513 / 513 cps	
		228 / 273 / 171 cps	
	LO	114 / 137 / 171 cps	
Resolution	Up to 360 x 360 dpi		
Throughput (ECMA 132)	457 pages per hour		
Character density	10, 12, 15, 17.1, 20 cpi		
Line density	2, 3, 4, 6, 8, 12 lpi		
Printhead lifetime	500 Mio. impact per wire		
RAM	256 kB		
Interface Standard	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6) USB Host		
Interface Optional	Serial RS-232		
Administration	Tally WebPanel via Ethernet; Config-Tool via USB/Parallel		
<b>Emulations Standard</b>		IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP	
	Epson FX 9-Nadel Emulation		
	LA Upgrade Kit: DEC PPL2		
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing		
Consumables	Ribbon: 10 Mio. characters		
Paper handling Standard	One tractor usable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off		
Paper handling Optional	Additional push tractor (rear)		
Copies	Push tractor front: 1 original + 5 copies;		
	Pull tractor top: 1 original + 5 copies;		
	Cut sheet: 1 original + 5 copies		
Paper types	Cut sheets, continuous forms, multi-part forms		
Paper weight	60-120 g/m <sup>2</sup>		
Paper format	Width: 76 to 278 mm; Length: 76 to 599 mm		
Weight	8,1 kg		
Dimensions	458 x 265 x 200 mm (W x D x H)		
Noise	<53 dB(A)		
Voltage	100 - 240 V autosensing		
Power consumption	60 Watt printing; <3 W Sleep Mode		
Temperature	+10° to +40° C; 10% to 85% rel. humidity		
Print volume	20.000 pages per month		
MTBF	25.000 hours @20% duty cyle		
Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022; SAP		

## **Configuration:**

• 2600+ Standard model

R. 1811-1816A | Nan Fung Centre 264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong Tel.: +852 2498 1507 | Fax: +852 2413 6047

