



2610+ High performance at low cost





HIGHLIGHTS AT A GLANCE:

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 24 wires print head for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- SB Host interface for easy firmwareupdate
- User-friendly, backlit illuminated LC display



2610+

The new Tally Dascom 2610+ is the **further developed variant** of the successful Tally Dascom 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 15 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB, Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only **up to 20% faster**, but also allows for a **noise reduction of up to 2 decibels** thanks to its design.

TECHNICAL DATA

Drint and	Fostost Chands COO and	
Print speed	Fastest Speed: 683 cps Character density 10 / 12 / 15 cpi	
	HS Draft 600 / 683 / 683 cps	
	Draft 513 / 513 cps	
	NLO 228 / 273 / 171 cps	
	LQ 114 / 137 / 171 cps	
Resolution	Up to360 x 360 dpi	
Throughput (ECMA 132)	457 pages per hour	
Character density	10, 12, 15, 17.1, 20 cpi	
Line density	2, 3, 4, 6, 8, 12 lpi	
Print head lifetime	500 Mio. impact per wire	
RAM	256 kB	
Interface Standard	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6) USB Host	
Interface Optional	Serial RS-232	
Administration	Tally WebPanel via Ethernet; Config-Tool via USB/Parallel	
Emulations Standard	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP	
	Epson FX 9-Nadel Emulation	
	LA Upgrade Kit: DEC PPL2	
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Bard and large character printing	codes
Consumables	Ribbon: 15 Mio. characters	
Paper handling Standard	One tractor usable as push (front or rear) or pull (top) version, continuous pape with straight paper path and park position, cut sheet front insertion, tear or fro	
Paper handling Optional	Additional push tractor (rear)	
Copies	Push tractor front: 1 original + 5 copies;	
	Pull tractor top: 1 original + 5 copies;	
	Cut sheet: 1 original + 5 copies	
Paper types	Cut sheets, continuous forms, multi-part forms	
Paper weight	60-120 g/m ²	
Paper format	Width: 76 to 420 mm; Length: 76 to 599 mm	
Weight	10,6 kg	
Dimensions	600 x 265 x 200 mm (W x D x H)	
Noise	<53 dB(A)	
<u>Voltage</u>	100 - 240 V autosensing	
Power consumption	60 Watt printing; <3 W Sleep Mode	
Temperature	+10° to +40° C; 10% to 85% rel. humidity	
Print volume	20.000 pages per month	
MTBF	25.000 hours @20% duty cyle	
Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022; SAP	

Configuration:

• 2610+ Standard model

