

NEW
Network model
with integrated
Ethernet interface

T5040

Robust, fast
and powerful



HIGHLIGHTS AT A GLANCE:

- Processing of diverse materials
- Automatic adjustment of print-head distance
- Automatic registration of forms, passports and passbooks
- Automatic paper edge detection
- Simultaneous connection to several systems via serial, parallel or USB and 2nd serial interface
- Unsurpassed processing time-typical passbook print in 2.2 seconds
- DIN letter printing in 11.8 seconds

T5040

With a speed up to 600 characters / sec. The T5040 processes a variety of print media, such as passports and pass-books, checks and receipts, through to A5 and A4 form sets. The flatbed design guarantees the safest paper handling, and additional features such as automatic document orientation and automatic print head spacing (AGA) provide unsurpassed ease of use.

The T5040 standard supports the printing of individual documents via the serial interface with a security protocol, as required in bank environments. By default, there is also a USB and parallel interface for flexible connections and for multi-user use. A model with a 2nd serial port is also available.

TECHNICAL DATA

| | |
|----------------------------|--|
| Print Speed | Fastest Speed: 600 cps Character density 10 / 12 / 15 cpi <i>HS Draft</i> 400 / 480 / 600 cps <i>Draft</i> 300 / 360 / 400 cps <i>LQ</i> 133 / 160 / 200 cps |
| Resolution | up to 360 x 360 dpi |
| Character Density | 10, 12, 15, 16.6, 17.1, 20 cpi |
| Line Density | 1, 2, 3, 4, 6, 8 lpi |
| Print Head Lifetime | 400 Million dots per pin |
| Memory | 256 kB |
| Interfaces | Standard Version: Parallel (Bi-directional), Serial (RS-232) and USB 2.0 N Version: Ethernet (10/100 BaseT), Parallel (Bi-directional), Serial (RS-232) and USB 2.0 2x serial Version: Parallel (Bi-directional), 2x Serial (RS-232) and USB 2.0 |
| Emulations | IBM 4722, IBM ProPrinter XL24e, Epson ESC P/2, Olivetti PR50/PR2/PRe |
| Fonts | Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic OCR-A/B, 10 Barcodes |
| Consumables | Ribbon: 10million characters |
| Paper Handling | Manual single sheet insertion from front, automatic paper alignment, automatic paper edge detection (left) |
| Copies | 1 original + 4copies |
| Paper Types | Single sheet, multi-part forms, passbooks and passports up to 2,0 mm thickness |
| Paper Weight | 60-260 g/m ² |
| Paper Format | Width: 70 to 240 mm; Length: 70 to 500 mm (Paper) Width: 105 to 235 mm; Length: 125 to 210 mm (Passbook/Passport opened) |
| Weight | 9,8 kg |
| Dimension | 378 x 280 x 168 mm (W x D x H) |
| Noise | 55 dB(A) |
| Power Voltage | 230 V - 50/60 Hz |
| Power Consumption | 9 W (Stand-By); 73 W (Printing) |
| Temperature | +10° to +40° C; 15% to 75% rel. humidity |
| Print Volume | 5.000 transactions per month |
| MTBF | 10.000 hours |
| Driver | Windows 8/8.1/10/11 and Server 2012/2016/2019/2022 |

Configurations:

- **T5040** Standard model
- **T5040 MSR-H** Model with horizontal magnetic stripe reader
- **T5040N** Model with integrated Ethernet

DASCOM GB Ltd
Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047