

PP 4060

18" CONTINUOUS FORM LASER PRINTER



PP 4060 with optional Stacker iPS 4050

- Two-Up support for A4 and Letter format, 18 inch paper width
- Performance: 63 pages per minute
- Paper width up to 457,2 mm (18 Zoll)
- Resolution 600 dpi
- 10BaseT/100BaseTX Ethernet interface
- Two different fanfold papers alternatively accessible
- Integrated paper cutter
- 45 scalable fonts and 13 resident barcodes
- Emulation: HP Laser Jet 4 (PCL 5e), IGP/ PGL

The PP 4060 printer is designed for a heavy duty workload of 300,000 pages per month.

Two independent tractor cassettes, the intelligent Paper Stacker, and the integrated cutting device provide the user with flexible paper management facilities.

Printing two-up on 18 inch wide media, the PP 4060 is perfectly suited for decentralized applications in network based environments such as banking, insurance, fulfillment services, and logistics.



PP 4060

18" CONTINUOUS FORM LASER PRINTER

Printer Specification

| | |
|----------------------------------|---|
| Print Speed: | up to 63 pages per minute (Letter Two-Up) up to 59 pages per minute (A4 Two-Up) up to 42 pages per minute (A4 landscape) up to 41 pages per minute (Letter landscape) up to 31 pages per minute (11" form length) up to 2,100 lines/minute at 6 lines/inch |
| Resolution: | 600 x 600 dpi |
| Workload: | 300,000 pages per month |
| Print Method: | Electrophotographic, LED array, organic photo-conductor, 2 component toner/developer, heat and pressure roller system with adjustable fusing temperature |
| Control Panel: | 7 inch color display with touch control |
| Diagnostics: | Selbsttest, Hexdump |
| Dimensions: | 890 mm x 350 mm x 780 mm (W x H x D) (inclusive tractor cassettes) |
| Weight: | 247 lbs. (112 kg) consumables included |
| Rated Voltage: | 100 - 110 V (-10/+6%) AC, 50 - 60 Hz / 12A 110 - 120 V (-10/+6%) AC, 50 - 60 Hz / 12A 220 - 240 V (-10/+6%) AC, 50 - 60 Hz / 6 A |
| Power Consumption: | |
| Operating power | < 1,200 W average (< 1,650 W peak) |
| Standby | < 400 W |
| Sleep mode | < 45 W |
| Environmental Conditions: | |
| operating | + 15 to + 35°C, 8 to 80 % rel. humidity. |
| storage consumables | - 20 to + 40°C, 95 % rel. humidity (40°C) |
| Sound Level: | < 55 dB(A) operating |
| Lifetime: | up to 12,000,000 pages (A4 landscape) |
| Agency Approvals: | CE, VDE / GS, UL, C-UL, FCC |

Connectivity

STANDARD INTERFACES AND EMULATIONS

| | |
|---------------------------|--|
| Interfaces: | Parallel IEEE 1284 Ethernet 10BaseT/100BaseTX |
| Emulationen / PDL: | HP LaserJet 4 (PCL 5e, PjL), HP - GL/2 PCL / PjL Extensions |
| Fonts: | 45 skalierbare Fonts, 10 bitmap fonts |
| Barcodes: | Code 39, Code 93, Code 128, Codabar, 2/5 industrial, 2/5 interleaved, EAN 8/13 Add on 2/5, Postnet, MSI, UPC-A, UPC-E, KIX-Code, Datamatrix Code |

Optional data stream converter available for IPDS and IGP.

Paper Handling

| | |
|-------------------------|---|
| Type: | Continuous forms and labels with tractor pin holes |
| Paper Transport: | Reversible paper motion, straight-through paper path |
| Paper Input: | Two independent, detachable tractor cassettes for fanfold paper |
| Paper Output: | directable to the rear (zero tear off or cut without loss of form) or to the top (stacker for cut sheets) |
| Paper Cutter: | Integrated cutting device separates print jobs or cuts fanfold paper into single sheets, enables change of forms without operator involvement |
| Paper Width: | min. 4 inch, max. 18 inch (print area 17 inch) |
| Page Length: | min. 3 inch (4 inch at upper output), max. 24inch if attached to stacker: min. 7 inch, max. 17 inch |
| Weight: | 64 g/m ² up to 155 g/m ² |

Control Unit

| | |
|-------------------------------------|--|
| Processor: | PowerPC |
| Data Memory: | 128 MB |
| Program and Font Memory: | 32 MB FLASH EPROM allows onsite software update |
| Stacker Control: | Supports attached intelligent Paper Stacker iPS 4050 |

Consumables

| | |
|------------------------|--|
| Toner Kit: | for A4 formats at 5% coverage up to 235,000 pages |
| Photoconductor: | up to 280,000 pages (A4 Two-Up) |
| Developer: | up to 430,000 pages (A4 Two-Up) |
| Fuser Unit: | up to 940,000 pages (A4 Two-Up) |

Optionen

| | |
|--------------------|--|
| iPS 4050: | Assures accurate stacking of forms up to 3,000 pages without operator involvement |
| Dimensions: | iPS: 1,060x 860 x 670 mm (WxHxD) printer / iPS: 1,120 x 1,160 x 780 mm (WxHxD) |

Printer drivers for all common Windows operating systems are available.
Printer configuration software and SAP R/3 Device Types can be loaded
from the PSI Laser website.

This is only an extract of the product specification. For a detailed specification it is referred
to the comprehensive product documentation.
Specifications are subject to change without notice. All registered trademarks are the
property of their respective companies.